



Insulation: one way to optimize the viscosity of gear oils and energy consumption in trucks

<https://library.fpinnovations.ca/en/permalink/fpipub43310>

Author: Ljubic, D.A.
Chinn, G.P.

Date: 1987

Material Type: Research report

Physical Description: 4 p.

Sector: Forest Operations

Field: Fibre Supply

Research Area: Forestry

Subject: Oil
Trucks
Viscosity


Series Number: Technical Notes

Language: English

Abstract: In an attempt to reduce fuel consumption and operation costs, especially during cold weather, the two drive axles of a logging truck were insulated to raise the temperatures of the lubricating oils. Thus the oil viscosity and consequently the energy losses owing to oils churning would be reduced. The temperature of the oil in the forward rear axle was recorded continuously for a 240 KM round trip of a logging truck. Insulation details have also been described.

Road transportation
Logging trucks
Tractor trailer combinations
Fuel consumption
Lubricating oils
VISCOSITY
AXLES
INSULATION


Documents



TN102.PDF

 Read Online

 Download



Wildfire suppressant rheology. Impact of water quality on water-enhancer viscosity

<https://library.fpinnovations.ca/en/permalink/fpipub8008>

Author: Refai, Razim

Yang, Junyi

Tsai, Peichun Amy

Contributor: University of Alberta

Date: October 2020

Material Type: Research report

Physical Description: 25 p.

Sector: Forest Operations

Field: Fibre Supply

Research Area: Wildfire Operations

Subject: Fire retardant

Retardant

Viscosity

Water

FPI TR

Series Number: Technical Report ; TR 2020 n.52

Location: Alberta

Language: English

Abstract: An important characteristic of the majority of the water-enhancing products on the wildfire suppression market is their ability to increase the viscosity of water. This increase in viscosity is linked to their performance. While performance of these products is key, there are several external variables that can influence how these suppressants physically behave. One such external variable is water quality, which is anecdotally known to impact water-enhancing products. This study aimed to understand how water quality—in particular, hardness—affects the viscosity of various water-enhancing products at different mix ratios. Understanding how water quality affects the viscosity of these products can offer insight into (1) which products are highly sensitive to water quality changes, and (2) how the target viscosity of a mixed product can be affected by water quality.

Documents



TR2020N52.PDF

 Read Online

 Download



Wildfire suppressant rheology. Mapping viscosity as a function of product mix ratios

<https://library.fpinnovations.ca/en/permalink/fpipub7858>

Author: Refai, Razim

Yang, Junyi

Tsai, Peichun Amy

Contributor: University of Alberta

Date: January 2021

Material Type: Research report

Physical Description: 20 p.

Sector: Forest Operations

Field: Fibre Supply

Research Area: Wildfire Operations

Subject: Fire retardant

Retardant

Viscosity

Water

FPI TR

Series Number: Technical Report ; TR 2021 n.3

Location: Alberta

Language: English

Abstract: The USDA Forest Service's Qualified Product List (QPL) provides guidance on the range of permissible mix ratios for water-enhancer products. Due to the proprietary nature of water-enhancer products, there are several unknowns about the rheology of the permissible mix ratios. This study focused on mapping the viscosity of various suppressant products as a function of their mix ratios. The results revealed a wide range of viscosities across products, with each product showing a different non-linear relationship with different mix ratios. The results from this study can help understand the optimum viscosity range to achieve desired drop characteristics during aerial operations.



TR2021N3.PDF

 Read Online

 Download